

Comment on “Testing integrability with a single bit of quantum information”

H. M. Wiseman

*Centre for Quantum Computer Technology, Centre for Quantum Dynamics, School of Science,
Griffith University, Brisbane 4111 Australia. email: h.wiseman@griffith.edu.au*

(Dated: February 9, 2008)

In quant-ph/0303042, Poulin, Laflamme, Milburn and Paz consider the problem of distinguishing quantum chaos from quantum integrability for dynamics in an N -dimensional Hilbert space. They claim that this can be done by deterministic quantum computing with a single bit using $O(\sqrt{N})$ physical resources, compared to $O(N)$ physical resources classically. I point out what seems to be a fatal flaw with their proposal.

Ref. [1] is concerned with the problem of determining whether the dynamics of a quantum system in an N -dimensional Hilbert space exhibit quantum chaos or quantum integrability. That is, whether the classical limit of the system is chaotic or integrable. This is a question of the properties of the distribution of the eigenvalue-spacing of the $N \times N$ Hamiltonian matrix H . They claim that this problem be solved using deterministic quantum computing with a single pseudo-pure qubit (DCQ1) [2] using $O(\sqrt{N})$ physical resources. For example, repeating the experiment $O(\sqrt{N})$ times, or using $O(\sqrt{N})$ computers in parallel, as in NMR quantum computing (QC) [3]. This represents a quadratic speed up over a classical computer, which requires $O(N)$ resources to find the N eigenvalues of H .

The crucial point of their proposal is at the end of their Sec. III. For the quantum algorithm to work, it is necessary to distinguish a signal difference of order $1/\sqrt{N}$ for a single computer. At this point they simply say “... which can be achieved using $O(\sqrt{N})$ physical resources.” Unfortunately, this seems not to be the case.

In a single qubit, if the signal (the mean value of σ_z ,

say) is small (of order $1/\sqrt{N}$ here), then the noise in a measurement of σ_z (“projection noise”) is of order unity. That is, the results $+1$ and -1 occur with almost equal probability so the variance in σ_z is almost 1. Now the *fundamental* signal to noise ratio (SNR) for an ensemble of such computers is proportional to $\sqrt{M}$, where M is the size of the ensemble. This is true whether M is the number of computers running in parallel, or the number of repetitions for a single computer. This is an elementary result in statistics: the signal rises as M but the noise rises as $\sqrt{M}$. Now to see the signal requires that the SNR be of order unity. Therefore one requires M of order N . That is, the resources scale the same as they do classically.

For relatively small M , the practical SNR in NMR QC may scale as M . This is because the noise may be limited by technical noise rather than fundamental projection noise, so the SNR rises with the signal. But that makes no difference to my proof because this argument is true only while technical noise is greater than projection noise. Thus the resources required can never be smaller than that required by projection noise, namely $O(N)$.

-
- [1] D. Poulin, R. Laflamme, G.J. Milburn, and J. P. Paz, quant-ph/0303042.
[2] E. Knill and R. Laflamme, Phys. Rev. Lett. **81**, 5672

- (1998).
[3] D.G. Cory et al., Fortschr. Phys. 48, 875 (2000).